

# Declaration of Performance



Force 8 Fabrications Ltd.

Unit 1c School St Trading Estate, Hazelgrove, Stockport, SK7 4RA

DoP No: 19- 28/05/13

Job No \_\_\_\_\_

Rehau S706 Internally Glazed Casement Window,  
Intended for use in domestic or commercial refurbishment or new building applications.

Annex ZA.1 of BS EN 14351-1:2006+A1:2010

Water-tightness: NPD

Dangerous substances: None released under normal indoor use.

Resistance to wind load: NPD

Load-bearing capacity of safety devices: Pass, 350N when fitted (1)

Acoustic performance: NPD

Thermal transmittance:  $\leq 1.6 \text{ W/m}^2\text{k}$  (2)

Radiation Properties: NPD

Air permeability: NPD

A Factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A1:2010.

(1) Report No. 2370/7933731/1of2/issue3, dated 20.12.2012 for Safety & Security friction hinges with built in restrictor - BSI, Notified Test Body No. 0086

(2) Thermal Transmittance calculation approved by Ventana Testing Services, Notified Test Body No. 1968, Ref Report No. CU13238-1 Dated:18/06/2013

Dennis Sumner  
Name (Print)

  
Signed

Managing Director  
Position

28/05/13 Force 8.  
Date and Place of Issue